

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E21B 47/022		A1	(11) International Publication Number: WO 99/66173 (43) International Publication Date: 23 December 1999 (23.12.99)
(21) International Application Number: PCT/EP99/03940 (22) International Filing Date: 14 June 1999 (14.06.99) (30) Priority Data: 98304821.6 18 June 1998 (18.06.98) EP (71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL). (71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA). (72) Inventor: HARTMANN, Robin, Adrianus; Volmerlaan 6, NL-2288 GD Rijswijk (NL).		(81) Designated States: AU, BR, CA, CN, IN, NO, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: METHOD OF DETERMINING AZIMUTH OF A BOREHOLE

(57) Abstract

A method is provided of determining an azimuth angle of a borehole formed in an earth formation using a magnetometer tool arranged in a drill string extending in the borehole, the magnetometer tool having a selected orientation relative to the drill string. The method comprises a) selecting at least two locations along the borehole at which the borehole has selected different borehole inclinations, b) for each selected location, arranging the drill string in the borehole such that the magnetometer tool is positioned at the selected location and operating the magnetometer tool so as to measure a local magnetic field including the earth magnetic field and a drill string magnetisation field having a component in a substantially vertical plane through the longitudinal axis of the drill string at the selected location, c) determining from the measured magnetic field and from the selected borehole inclinations, said component of the drill string magnetisation field, d) correcting the measured magnetic field for said component of the drill string magnetisation field, and e) determining from the corrected magnetic field, the borehole azimuth.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD OF DETERMINING AZIMUTH OF A BOREHOLE

The present invention relates to a method of determining an azimuth angle of a borehole formed in an earth formation using magnetometer tool arranged in a drill string extending longitudinally in the borehole.

5 During drilling of a borehole in an earth formation it is generally desirable to check the borehole course by measuring the inclination and azimuth of the borehole at regular intervals. The borehole inclination can be determined using accelerometer measurements in the

10 borehole and the Earth gravity field as a reference. The borehole azimuth is determined using a package of magnetometers included in the Bottom Hole Assembly (BHA) of the drill string. The magnetometers are operated to measure the components of the local magnetic field from

15 which the borehole azimuth is determined using the Earth magnetic field as a reference. In many instances however the measured local magnetic field includes, apart from the Earth magnetic field components, components attributable to drill string magnetisation. In order to

20 obtain sufficiently accurate azimuth data it is required that such drill string magnetisation effects are taken into account.

EP-A-0 193 230 discloses a method of determining azimuth of a borehole formed in an earth formation using

25 a magnetometer package included in a drill string extending into the borehole, wherein the effect of drill string magnetisation is taken into account by first eliminating the effect of cross-axial drill string magnetisation prior to eliminating the influence of axial

30 drill string magnetisation. The cross-axial drill string magnetisation is eliminated by taking so-called

rotational shots, i.e. by measuring the local magnetic field at different rotational locations of the magnetometer tool and determining the cross-axial drill string magnetisation from the magnetic field data thus obtained. The axial drill string magnetisation is computed from the measured magnetic field and from the Earth magnetic field. Once the measured magnetic field has been corrected for cross-axial and axial drill string magnetisation, the borehole azimuth is determined from the corrected field and from the Earth magnetic field which is generally known for most places on Earth. The computed azimuth however is very sensitive to inaccuracies in the Earth magnetic field data, especially in case of highly inclined boreholes extending substantially in east or west direction.

It is an object of the invention to provide an improved method of determining azimuth of a borehole, which method is less sensitive to inaccuracies in the Earth magnetic field data even for highly inclined boreholes extending substantially in east or west direction.

In accordance with the invention there is provided a method of determining an azimuth angle of a borehole formed in an earth formation using a magnetometer tool arranged in a drill string extending in the borehole, the magnetometer tool having a selected orientation relative to the drill string, the method comprising

- a) selecting at least two locations along the borehole at which the borehole has selected different borehole inclinations;
- b) for each selected location, arranging the drill string in the borehole such that the magnetometer tool is positioned at the selected location and operating the magnetometer tool so as to measure a component of a local magnetic field along an axis having a selected

orientation relative to the magnetometer tool, the local magnetic field including the earth magnetic field and a drill string magnetisation field;

- 5 c) determining from the measurements and from the selected borehole inclinations, a contribution from the drill string magnetisation field to the measured components;
- d) correcting the measurements for said contribution from the drill string magnetisation field; and
- 10 e) determining from the corrected measurements, the borehole azimuth.

The contribution from the earth magnetic field to each measured component along the axis of selected orientation is different for the different borehole
15 locations because the drill string, and therefore also said axis, is oriented differently relative to the earth magnetic field at the different locations. On the other hand, the contribution from the drill string magnetisation field to the measured component is the same
20 for the different borehole locations because the orientation of said axis relative to the drill string magnetisation field does not change. Since the orientation of said axis is directly related to the orientation of the drill string and therefore to the
25 borehole inclination, the contribution from the drill string magnetisation field to the measured component can be determined from the difference between the measured components at the different locations and from the different borehole inclinations at the different
30 locations. An example of such determination is presented in the detailed description below.

Preferably said component of the local magnetic field is the axial component of the local magnetic field, which is the component in axial direction of the drill string.
35 It is to be understood that the contribution from the

drill string magnetisation field to the cross-axial component (if any at all) of magnetic field generally is an order of magnitude smaller than the axial contribution. Therefore, for most applications it is sufficiently accurate to disregard such cross-axial contribution. Alternatively, the measured magnetic field can be corrected for a cross-axial contribution from the drill string magnetisation field prior to step c).

The method can suitably be applied for a borehole of which the longitudinal axis at the selected locations is substantially located in a vertical plane.

For most applications it is sufficient to select two said locations of different borehole inclination.

For enhanced accuracy in applying the method of the invention, the borehole inclinations at at least two of said locations differ from each other by an angle of at least 40° .

In case the borehole inclination at a first one of the locations is less than 45° it is preferred to determine the contribution to the axial components attributable to drill string magnetisation from the vertical component of the Earth magnetic field. If furthermore the drill string magnetisation at the first location is different than at a second one of the locations, e.g. due to different Bottom Hole Assemblies, the borehole inclination angle at the second location is suitably between 80° - 100° .

Conversely, in case the wellbore inclination at the first location exceeds 45° it is preferred to determine the contribution to the axial components attributable to drill string magnetisation from the horizontal component of the Earth magnetic field. If furthermore the drill string magnetisation at the first location is different than at the second location, the borehole inclination

angle at the second location is suitably between 0° and $+10^\circ$.

The invention will be described further in more detail and by way of example with reference to the accompanying drawings in which

Fig. 1 shows a horizontal plane of the (N,E,V) coordinate system;

Fig. 2 shows a vertical plane through line H of the coordinate system of Fig. 1;

Fig. 3 shows a borehole-fixed coordinate system (HS, HSR, z) and a tool-fixed coordinate system (x,y,z).

In Fig. 1 is shown the horizontal N-E plane of the North (N), East (E), Vertical (V) coordinate system, wherein line H is a projection in the N-E plane of the longitudinal axis of a borehole 10 (Fig. 3) and angle A indicates the borehole azimuth. It is to be understood that angle A may vary along the length of the borehole. B_N represents the horizontal vector component of the earth magnetic field.

In Fig. 2 is shown a vertical plane through line H. Line T represents the longitudinal axis of the borehole and angle I the borehole inclination which varies along the length of the borehole. B_V represents the vertical vector component of the earth magnetic field and $B_N \cos A$ is the projection of the horizontal component of the earth magnetic field on line H.

In Fig. 3 is shown a cross-sectional view of the borehole 10, a co-ordinate system (HS, HSR, z) fixed to the borehole 10 and a co-ordinate system (x, y, z) fixed to a magnetometer tool (not shown) for measuring the components of a local magnetic field \underline{B} in the (x, y, z) co-ordinate system. The magnetometer tool is fixedly arranged in a drill string (not shown) extending through the borehole, therefore the (x, y, z) co-ordinate system

can be thought of as being fixed to the drill string. The HS-, HSR-, x-, and y-axes extend in the transverse plane of the borehole at point P whereby the x-, y-axes are rotated relative to the HS-, HSR-axes about an angle α which is referred to as the tool-face angle. The z-axis extends in longitudinal direction of the borehole 10. The drill string is furthermore provided with an accelerometer tool (not shown) for measuring the components of the earth gravity field \underline{G} in the (x, y, z) co-ordinate system.

During normal operation the magnetometer tool measures the components B_x , B_y , B_z of the local magnetic field vector \underline{B} and the accelerometer tool measures the components G_x , G_y , G_z of the gravity field vector \underline{G} while the drill string is kept stationary. The tool-face angle α and the inclination angle I are determined from the equations:

$$G_{HS} = G_x \cos \alpha - G_y \sin \alpha \quad (1)$$

$$G_v = G_z \cos I - G_{HS} \sin I \quad (2)$$

$$G_z \sin I + G_{HS} \cos I = 0 \quad (3)$$

wherein

G_{HS} is the component of \underline{G} in HS-direction;

G_v is the (known) component of \underline{G} in V-direction.

From the measured magnitudes of B_x , B_y , B_z and from the tool face angle α , the components of \underline{B} in the (HS, HSR, z) co-ordinate system are determined thus yielding the local magnetic field vector (B_{HS} , B_{HSR} , B_z). These components include contributions from the earth magnetic field and from drill string magnetisation. Denoting the earth magnetic field vector by (B_{HS}^e , B_{HSR}^e , B_z^e) and the drill string magnetisation vector by (C_{HS} , C_{HSR} , C_z) the local magnetic field vector is

$$\begin{aligned} (B_{HS}, B_{HSR}, B_z) &= (B_{HS}^e, B_{HSR}^e, B_z^e) + \\ (C_{HS}, C_{HSR}, C_z) \end{aligned} \quad (4)$$

The cross-axial contributions from drill string magnetisation are then determined and eliminated from the magnetic field vector, for example by means of a "rotational shot" whereby a number of surveys are taken at various rotational angles of the magnetometer tool in the borehole as described in EP-A-0 193 230. After such elimination the local magnetic field vector is

$$(B_{HS}, B_{HSR}, B_z) = (B_{HS}^e, B_{HSR}^e, B_z^e + C_z) \quad (5)$$

The sum of the vertical components of B_{HS}^e and B_z^e is equal to the vertical component B_v of the magnetic field (B_{HSR}^e has no vertical component), thus yielding

$$B_v = -B_{HS}^e \sin I + B_z^e \cos I$$

and from eq. (5)

$$B_v = -B_{HS}^e \sin I + (B_z - C_z) \cos I \quad (6)$$

By operating the magnetometer tool at two borehole locations with different inclinations I_1 and I_2 two local magnetic field vectors $(B_{HS1}, B_{HSR1}, B_{z1})$ and $(B_{HS2}, B_{HSR2}, B_{z2})$ are obtained, and from eq. (6) it follows

$$B_v = -B_{HS}^e \sin I_1 + (B_{z1} - C_{z1}) \cos I_1 \quad (7)$$

$$B_v = -B_{HS}^e \sin I_2 + (B_{z2} - C_{z2}) \cos I_2 \quad (8)$$

Axial drill string magnetisation depends primarily on the magnetic properties of the BHA, not on borehole inclination. Therefore it is considered that at least as long as the BHA is not changed:

$$C_{z1} = C_{z2} = C_z \quad (9)$$

Equations (7), (8), (9) contain the unknowns B_v , C_{z1} and C_{z2} . The inclinations I_1 and I_2 are known from measurements using one or more accelerometer meters included in the drill string. It is found that

$$C_z(\cos I_2 - \cos I_1) = B_{HS}^e \sin I_1 - B_{z1} \cos I_1 - B_{HS}^e \sin I_2 + B_{z2} \cos I_2 \quad (10)$$

from which C_z is determined.

5 The local magnetic field at each point can now be corrected for axial drill string magnetisation.

The above approach is preferred for low borehole inclinations, i.e. inclinations less than 45° , because C_z then is relatively insensitive to variations in borehole inclination.

10 For borehole inclinations beyond 45° the following approach is preferred.

The sum of the components of B_{HS}^e and B_z^e in direction H is equal to the component of the earth magnetic field in direction H, thus yielding

$$15 \quad B_n \cos A = B_{HS}^e \cos I + B_z^e \sin I \quad (11)$$

or

$$B_n \cos A = B_{HS}^e \cos I + (B_z - C_z) \sin I \quad (12)$$

For two points with respective inclinations I_1, I_2 and azimuth A_1, A_2 it follows that

$$20 \quad B_n \cos A_1 = B_{HS}^e \cos I_1 + (B_{z1} - C_{z1}) \sin I_1 \quad (13)$$

$$B_n \cos A_2 = B_{HS}^e \cos I_2 + (B_{z2} - C_{z2}) \sin I_2 \quad (14)$$

The HSR components of the local magnetic field, corrected for cross-axial drill string magnetisation as described above, for the two points are

$$25 \quad B_{HSR}^e \sin A_1 = -B_n \sin A_1 \quad (15)$$

$$B_{HSR}^e \sin A_2 = -B_n \sin A_2 \quad (16)$$

From eqs. (13) - (16), and with $C_{z1} = C_{z2} = C_z$ (e.g. for unchanged BHA), it follows that

$$30 \quad (B_{HSR}^e \sin A_1)^2 + (B_{HS}^e \cos I_1 + (B_{z1} - C_z) \sin I_1)^2 - (B_{HSR}^e \sin A_2)^2 + (B_{HS}^e \cos I_2 + (B_{z2} - C_z) \sin I_2)^2 -$$

$$C_z) \sin I_2))^2 = 0 \quad (17)$$

Eq. (17) is a quadratic expression in C_z with generally two solutions for C_z . The solution which gives a horizontal magnetic field component closest to the expected horizontal magnetic field component is to be selected from the two. The local magnetic field at each point can then be corrected for axial drill string magnetisation.

If different BHA's are used during the measurements at the different survey points C_{z1} is generally not equal to C_{z2} . Therefore it is preferred that for the low inclination mode, i.e. when using eq. (10), at least one survey point is at a borehole inclination between 80° - 100° , preferably about 90° , because then one of the components $C_{z1} \cos I_1$ or $C_{z2} \cos I_2$ in eqs. (7), (8) substantially vanishes.

Similarly, it is preferred that for the high inclination mode, i.e. when using eq. (17), at least one survey point is at a borehole inclination between 0° and $+10^\circ$, preferably about 0° , because then either $C_{z1} \sin I_1$ or $C_{z2} \sin I_2$ in eq. (17) substantially vanishes.

Instead of using two survey points as described above, more than two survey points can be used to correct for axial drill string magnetisation.

C L A I M S

1. A method of determining an azimuth angle of a borehole formed in an earth formation using a magnetometer tool arranged in a drill string extending in the borehole, the magnetometer tool having a selected orientation relative to the drill string, the method comprising
- 5 a) selecting at least two locations along the borehole at which the borehole has selected different borehole inclinations;
- 10 b) for each selected location, arranging the drill string in the borehole such that the magnetometer tool is positioned at the selected location and operating the magnetometer tool so as to measure a component of a local magnetic field along an axis having a selected
- 15 orientation relative to the magnetometer tool, the local magnetic field including the earth magnetic field and a drill string magnetisation field;
- 20 c) determining from the measurements and from the selected borehole inclinations, a contribution from the drill string magnetisation field to the measured components;
- 25 d) correcting the measurements for said contribution from the drill string magnetisation field; and
- e) determining from the corrected measurements, the borehole azimuth.
2. The method of claim 1, wherein the longitudinal axis of the borehole at the selected locations is substantially located in a vertical plane.
3. The method of claim 1 or 2, wherein the borehole inclinations at at least two of said locations differ
- 30 from each other by an angle of at least 40°.

4. The method of any one of claims 1-3, wherein said component of the local magnetic field is the axial component of the local magnetic field.

5. The method of claim 4, wherein the borehole inclination at a first one of said locations is less than 45° and wherein step c) comprises determining the contribution from axial component of the drill string magnetisation from the relationship:

$$C_z (\cos I_2 - \cos I_1) = B_{HS}^e I_1 \sin I_1 - B_{z1} \cos I_1 - B_{HS}^e I_2 \sin I_2 - B_{z2} \cos I_2$$

as defined hereinbefore.

6. The method of claim 5, wherein the drill string magnetisation for the magnetometer tool at the first location is different than for the magnetometer tool at the second location, and wherein the borehole inclination angle at the second location is between 80°-100°.

7. The method of claim 4, wherein the borehole inclination angle at a first one of said locations exceeds 45° and wherein step c) comprises determining the axial component of the drill string magnetisation from the relationship:

$$(B_{HSR}^e I_1)^2 + (B_{HS}^e I_1 \cos I_1 + (B_{z1} - C_{z1}) \sin I_1)^2 - (B_{HSR}^e I_2)^2 + (B_{HS}^e I_2 \cos I_2 + (B_{z2} - C_{z2}) \sin I_2)^2 = 0$$

as defined hereinbefore.

8. The method of claim 7, wherein the drill string magnetisation for the magnetometer tool at the first location is different than for the magnetometer tool at the second location, and wherein the borehole inclination angle at the second location is between 0° and +10°.

9. The method of any one of claims 1-8, wherein the magnetometer tool determines the components of the local magnetic field in a co-ordinate-system having a primary axis substantially in axial direction of the borehole, a

secondary axis substantially in high-side direction of the borehole, and a tertiary axis substantially in high-side right direction of the borehole.

5 10. The method of any one of claims 1-9, wherein two said locations are selected along the borehole.

11. The method substantially as described hereinbefore with reference to the drawings.

1/1

Fig.1.




Fig.2.





Fig.3.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03940

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 E21B47/022

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 435 069 A (NICHOLSON JAMES W) 25 July 1995 (1995-07-25) the whole document. ---	1, 3, 10
X	US 5 321 893 A (ENGEBRETSON HAROLD J) 21 June 1994 (1994-06-21) column 5, line 21 - line 56 column 6, line 3 - line 4 column 10, line 3 - line 17 ---	1, 3, 10
A	EP 0 193 230 A (SHELL INT RESEARCH) 3 September 1986 (1986-09-03) cited in the application abstract --- -/--	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

24 September 1999

Date of mailing of the international search report

13.10.99

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hoekstra, F

INTERNATIONAL SEARCH REPORT

In tional Application No

PCT/EP 99/03940

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 96 02733 A (BAKER HUGHES INC ; BROOKS ANDREW GOODWIN (US)) 1 February 1996 (1996-02-01) abstract ---	1
A	US 4 709 486 A (WALTERS PHILIP H) 1 December 1987 (1987-12-01) abstract -----	1

INTERNATIONAL SEARCH REPORT

International application No.
PCT/EP 99/03940

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 11
because they relate to subject matter not required to be searched by this Authority, namely:
Claim 11 not allowed according to Rule 6.2(a) PCT
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

In tional Application No

PCT/EP 99/03940

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5435069 A	25-07-1995	AU 675691 B	13-02-1997
		AU 5883494 A	15-08-1994
		BR 9405808 A	19-12-1995
		CN 1116440 A	07-02-1996
		DE 69402530 D	15-05-1997
		DK 679216 T	08-12-1997
		WO 9416196 A	21-07-1994
		EP 0679216 A	02-11-1995
		JP 8505670 T	18-06-1996
		NO 952745 A	11-07-1995
		NZ 259867 A	25-09-1996
		ZA 9400154 A	18-08-1994
US 5321893 A	21-06-1994	CA 2112777 A	27-08-1994
		GB 2275536 A, B	31-08-1994
EP 0193230 A	03-09-1986	AU 570356 B	10-03-1988
		AU 5389886 A	04-09-1986
		BR 8600773 A	04-11-1986
		CA 1259187 A	12-09-1989
		CN 1017739 B	05-08-1992
		DK 83986 A	27-08-1986
		EG 17892 A	30-11-1991
		IN 167045 A	25-08-1990
		US 4682421 A	28-07-1987
WO 9602733 A	01-02-1996	AU 7190294 A	16-02-1996
US 4709486 A	01-12-1987	NONE	